


额定负荷	DC 12V/50mA	
接触电阻	100mΩ max.	
绝缘电阻	DC100V 60S 100MΩ min.	
抗电强度	AC250V/(50~60HZ) 60S min.	
操作力	160±50gf	250±50gf
寿命试验	100,000 cycles	70,000 cycles
行程	Tavels 0.25±0.1mm	



安装尺寸图

轻触开关	编带
材质:	非编带, 不启用

初始颜色，则不启用

— 材质：
0=初始材质
1=新增材质
依次增加

— 产品高度(H)：
430=4.3mm
900=9.0mm

5	COVER	1	Stainless Steel	NATURAL
4	ACTUATOR	1	PPA	BLACK
3	DOVE	1	Phosphor Bronze/Ag	Ag-PLATED
2	TERMINAL	1	BRASS	Ag-PLATED
1	HOUSING	1	PPA	BLACK
ITEM	PART NAME	QUANTITY	MATERIAL	FINISH
X. ± 0.3	X. ± 3'	UNITS	MM	NAME(INTENDED USE)
.X ± 0.2	.X ± 2'	MAT'L		6X6 SERIES TACT SWITCH
.XX ± 0.1	.XX' ± 1'			PART NO.(INTENDED USE)
.XXX ± 0.05	.XXX' ± 0.5'	FINISH		1TS005F-****-****1
				PRODUCT DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON YUAN PRECISION IN CO., LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON YUAN